

SECTION 09 6513 - RESILIENT BASE AND ACCESSORIES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
1. Resilient base.
  2. Resilient stair accessories.
  3. Resilient molding accessories.

1.3 ACTIOLT D Tw -9.482 -19i0 Tc 0 Tw 1.398 0 Td ( )Tj -0.T700m522.6-12.3d ( )Tj .3R11.398c4lm5221bH2 <<0 Tc

B. LEED Submittals:

1. Product Data for Credit IEQ 4.1: For adhesives, documentation including printed statement of VOC content.
  2. Product Data for Credit IEQ 4.3: For adhesives, documentation including printed statement of VOC content.
  3. Product Data for Credit IEQ 4.3: For resilient stair accessories, documentation from an independent testing agency indicating compliance with the FloorScore standard.
- C. Samples: For each exposed product and for each color and texture specified, not less than 12 inches (300 mm) long.
- D. Samples for Initial Selection: For each type of product indicated.
- E. Samples for Verification: For each type of product indicated and for each color, texture, and pattern required in manufacturer's standard-size Samples, but not less than 12 inches (300 mm) long.
- F. Product Schedule: For resilient base and accessory products. Use same designations indicated on Drawings.

1.4 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.

NORTHWESTERN UNIVERSITY  
PROJECT NAME \_\_\_\_\_  
JOB # \_\_\_\_\_

FOR: \_\_\_\_\_  
ISSUED: 03/29/2017



NORTHWESTERN UNIVERSITY  
PROJECT NAME \_\_\_\_\_  
JOB # \_\_\_\_\_

FOR: \_\_\_\_\_  
ISSUED: 03/29/2017

2.4 RUBBER MOLDING ACCESSORY

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
  - 1. Armstrong World Industries, Inc.
  - 2. Burke Mercer Flooring Products; a division of Burke Industries Inc.
  - 3. Johnsonite; a Tarkett company.
  - 4. Roppe Corporation, USA.
- B. Description: Rubber [stair-tread nosing] [carpet edge for glue-down applications] [nosing for carpet] [nosing for resilient flooring] [reducer strip for resilient flooring] [joiner for tile and carpet] [transition strips].
- C. Profile and Dimensions: [As indicated] <Insert profile and dimensions>.
- D. Locations: Provide rubber molding accessories in areas indicated on the drawings.
- E. Colors and Patterns: As selected by Architect from full range of industry colors.

2.5 INSTALLATION MATERIALS

- A. Trowelable Leveling and Patching Compounds: Latex-modified, portland cement based or blended hydraulic-cement-based formulation provided or approved by resilient-product manufacturer for applications indicated.
- B. Adhesives: Water-



NORTHWESTERN UNIVERSITY  
PROJECT NAME \_\_\_\_\_  
JOB # \_\_\_\_\_

FOR: \_\_\_\_\_  
ISSUED: 03/29/2017

- E. Do not stretch resilient base during installation.
- F. On masonry surfaces or other similar irregular substrates, fill voids along top edge of resilient base with manufacturer's recommended adhesive filler material.
- G. Preformed Corners: Install preformed corners before installing straight pieces.

#### 3.4 RESILIENT ACCESSORY INSTALLATION

- A. Comply with manufacturer's written instructions for installing resilient accessories.
- B. Resilient Stair Accessories:
  - 1. Use stair-tread-nose filler to fill nosing substrates that do not conform to tread contours.
  - 2. Tightly adhere to substrates throughout length of each piece.
  - 3. For treads installed as separate, equal-length units, install to produce a flush joint between units.
- C. Resilient Molding Accessories: Butt to adjacent materials and tightly adhere to substrates throughout length of each piece.